

### TECHNICAL FEATURES

Monobloc enclosure, roof, door and rear panel manufactured from aluminium alloy AlMg3 or sheet steel.

- welded monobloc structure with removable rear panel (single walled version); welded monobloc structure with removable rear panel and provided with external covers (double walled version)
- rear and side covers fixed to the monobloc structure without the aid of screws, with a pre-defined mounting sequence and a logical system of joint (only for double walled version)
- roof with ventilation slots and screwed to the monobloc enclosure (even hinged for double walled version)
- exclusive frontal access with a door provided with a two-component polyurethane foam seal, 3 points lever-operated locking system and key lock
- 40 mm high rain canopy with a 20 mm overhang on all sides
- removable and screwed cable entry plates
- available with the double door for W=1200 mm
- plinth H=100/200 available with front blank or ventilated crosspieces\*.

\* Plinth to be ordered separately

\*\* Solution with two-component silicone foam seal available upon request.

Thanks to the specific constructive concept, high quality materials and resistant finishes, EVIS range of outdoor solutions provides the perfect protection from environmental factors, extreme temperatures, direct sunlight, harsh environment, vandalism and atmospherically, chemical and mechanical agents.



Possibility to design solutions with special dimensions, different finishes, special insulations, silicone seal or completely customised solutions according to customers' requirements.

### PAINT FINISH

- Mild steel version: double layer of special powder coating: epoxy polyester resin primer and second polyester layer with anticorrosion pigments (RAL 7035 smooth for the cabinet, Pantone 2717U smooth for roof and plinth)
- Aluminium alloy version: special painting process with a single polyester powder coating with zinc base (RAL7035 smooth for enclosure, Pantone 2717U smooth for roof and plinth).

### PROTECTION RATING

- IP56 (single door) and IP55 (double door) complying with IEC EN62208; EN60529
- Protection degree guaranteed by the two-component foam seal\*\*
- Impact resistance IK 10 complying with IEC EN62208; EN62262.

\* Plinth to be ordered separately.

\*\* Solution with two-component silicone foam seal available upon request.

CODE		U	DIMENSIONS (MM)		
ALUMINIUM	STEEL		WIDTH	HEIGHT	DEPTH
OUTDOOR CABINET ABACUS EVIS PRO - SINGLE-WALL					
EVIS060804SA	EVIS060804SM	15	600	800	400
EVIS061204SA	EVIS061204SM	24	600	1200	400
EVIS061205SA	EVIS061205SM	24	600	1200	500
EVIS061404SA	EVIS061404SM	29	600	1400	400
EVIS080804SA	EVIS080804SM	15	800	800	400
EVIS081204SA	EVIS081204SM	24	800	1200	400
EVIS081205SA	EVIS081205SM	24	800	1200	500
EVIS081404SA	EVIS081404SM	29	800	1400	400
EVIS120804SA	EVIS120804SM	15	1200	800	400
EVIS121204SA	EVIS121204SM	24	1200	1200	400
EVIS121205SA	EVIS121205SM	24	1200	1200	500
EVIS121404SA	EVIS121404SM	29	1200	1400	400
OUTDOOR CABINET ABACUS EVIS PRO - DOUBLE-WALL					
EVIS060804DA	EVIS060804DM	15	600	800	400
EVIS061204DA	EVIS061204DM	24	600	1200	400
EVIS061205DA	EVIS061205DM	24	600	1200	500
EVIS061404DA	EVIS061404DM	29	600	1400	400
EVIS080804DA	EVIS080804DM	15	800	800	400
EVIS081204DA	EVIS081204DM	24	800	1200	400
EVIS081205DA	EVIS081205DM	24	800	1200	500
EVIS081404DA	EVIS081404DM	29	800	1400	400
EVIS120804DA	EVIS120804DM	15	1200	800	400
EVIS121204DA	EVIS121204DM	24	1200	1200	400
EVIS121205DA	EVIS121205DM	24	1200	1200	500
EVIS121404DA	EVIS121404DM	29	1200	1400	400

Note: Further dimensions available on request.

PRODUCT CODE				DESCRIPTION
ALUMINIUM		MILD STEEL		
BLANK	VENTILATED	BLANK	VENTILATED	
OUTDOOR CABINET ABACUS EVIS PRO – MODULAR PLINTH				
EVZE-T0400A	EVZE-T0400AV	EVZE-T0400M	EVZE-T0400MV	DEPTH MEMBER WITH INTEGRATED CORNERS H=100
EVZE-T0500A	EVZE-T0500AV	EVZE-T0500M	EVZE-T0500MV	DEPTH MEMBER WITH INTEGRATED CORNERS H=100
EVZE-T0600A	EVZE-T0600AV	EVZE-T0600M	EVZE-T0600MV	FRONT CROSS MEMBER (2 PCS)
EVZE-T0800A	EVZE-T0800AV	EVZE-T0800M	EVZE-T0800MV	FRONT CROSS MEMBER (2 PCS)
EVZE-T1200A	EVZE-T1200AV	EVZE-T1200M	EVZE-T1200MV	FRONT CROSS MEMBER (2 PCS)

DEPTH RAILS 1.5mm GALVANISED STEEL			
WTPR CODE	CABINET DEPTH	RAIL LENGTH	NOTES:
WTPR-050040	400	300	1.ACCESSORY FIXING BRACKET AND ALSO ALLOWS 19" PANELS TO BE POSITIONED AT VARIOUS DEPTHS. 4 / KIT
WTPR-050050	500	400	
WTPR-050060	600	500	
WTPR-050080	800	700	
WTPR-050120	1200	1100	
WTPR-050140	1400	1300	2.FIXING BRACKETS WTSF-001 TO BE ORDERED SEPERATELY

19" PANEL MOUNTS 1.5mm STEEL RAL7035 (2/KIT)			
WTMK CODE	CABINET HEIGHT	U	NOTES:
WTMK150800	800	15	1. NOT AVAILABLE FOR 1200 WIDE CABINET 2. FOR 800 WIDE CABINET ORDER WTTK000800 SEPERATELY
WTMK241200	1200	24	
WTMK291400	1400	29	