

#### 4K 60Hz KVM

- 4K KVM with 8 HDMI USB ports in 1U
- 4K KVM cables support DP & HDMI video input
- USB hub port share peripheral devices among computers
- Local console & KVM ports support resolution 4K, 2K and 1080p.
- Multi-platform for PC, server, blade server & SUN / MAC
- Port switching via front button & keyboard hotkeys
- Hot pluggable, no software or drivers required



#### 2K KVM

- 2K KVM with 8 HDMI USB ports in 1U
- 2K KVM cables support DVI-D & HDMI video input
- Local console & KVM ports support resolution 2K and 1080p.
- Multi-platform for PC, server, blade server & SUN / MAC
- Port switching via front button & keyboard hotkeys
- Hot pluggable, no software or drivers required



#### DVI-D KVM

- DVI-D KVM with 12 ports in 1U
- Local console & KVM ports support resolution up to 1920 x 1200
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Port switching via front button & keyboard hotkeys
- Hot pluggable, no software or drivers required



#### CAT6 MATRIX KVM

- CAT6 KVM with 16 or 32 Ports in 1U
- Simultaneous & independent access up to 4 consoles
- Cat6 dongle available for DP, HDMI, DVI-D or VGA video input
- Local console & KVM ports support resolution up to 1920 x 1080
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Cascade levels up to 8 KVM switches



#### IP-S101

IP Combo KVM Extender

- Compatible with all branded KVM switches
- IP Remote access from any location via web browser
- Maintaining servers across the world up to BIOS level



**For further details on KVM Products please contact the Cannon Sales Team.**

Size conversions: 1U = 44.45mm = 1 3/4" 600mm = 24" 700mm = 28" 800mm = 32" 1kg = 2.2lbs

T: +44(0)1425 632600 | CANNONTECH.CO.UK | SALES@CANNONTECH.CO.UK

### MATRIX DB-15 KVM

- DB-15 KVM with 8 or 16 ports in 1U
- Simultaneous & independent access up to 4 consoles
- Local console & KVM ports support resolution up to 1920 x 1080
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Cascade levels up to 8 KVM switches



### CAT6 COMBO KVM

- Cat6 KVM with 8, 16 or 32 ports in 1U
- Cat6 dongle available for DP, HDMI, DVI-D or VGA video input
- Local console & KVM ports support resolution up to 1920 x 1200
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Cascade levels up to 8 KVM switches



### DB-15 USB HUB KVM

- DB-15 KVM with 8 or 16 ports in 1U
- USB hub ports share peripheral devices among computers
- Local console & KVM ports support resolution up to 1920 x 1200
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required



### DB-15 COMBO KVM

- DB-15KVM with 8 or 16 Ports in 1U
- Local console & KVM ports support resolution up to 1920 x 1200
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Cascade levels up to 8 KVM switches



### SUN-31 kit

#### PS/2 to USB Adapter

- Convert PS/2 keyboard and mouse to the USB Interface
- Convert PS2 KVM switches to USB KVM switches
- Supports standard PS/2 mouse and Microsoft IntelliMouse
- Easy to Install
- Bus power, no external power required
- Complies to USB 1.0 and 1.1 specification
- Support UHCI and OHCI USB interface



**For further details on KVM Products please contact the Cannon Sales Team.**

Size conversions: 1U = 44.45mm = 1 3/4" 600mm = 24" 700mm = 28" 800mm = 32" 1kg = 2.2lbs

T: +44(0)1425 632600 | CANNONTECH.CO.UK | SALES@CANNONTECH.CO.UK