

TECHNICAL FEATURES

Enclosure manufactured from sheet steel, supplied with cable entry and blank reversible door, complete with 1 pair of 19" rack profiles mounted to the front.

Enclosure suitable for the assembly of both nr. 2 additional rack profiles on the back and the mounting plate. Rack profiles manufactured from galvanized sheet steel.

PAINT FINISH

- Epoxy polyester powder coating.
- Enclosure and door: colour RAL 7035 textured finish.

SUPPLY

- Enclosure Body
- Door provided with locking system with \varnothing 3mm double bar key
- 1 pair of 19" rack mounting profiles
- Cable entry plate with sealing gasket
- Screws for earth connection and mounting accessories.



ORDER CODES					
Height U	Width mm	Height mm	Depth mm	With Plain Door	With Glazed Door
10	600	500	400	APRO6540B	APRO6540BV
10	600	500	500	APRO6550B	APRO6550BV
10	600	500	600	APRO6560B	APRO6560BV
13	600	600	400	APRO6640B	APRO6640BV
13	600	600	500	APRO6650B	APRO6650BV
13	600	600	600	APRO6660B	APRO6660BV
17	600	800	400	APRO6840B	APRO6840BV
17	600	800	500	APRO6850B	APRO6850BV
17	600	800	600	APRO6860B	APRO6860BV

Note: Further dimensions available on request.

PROTECTION RATING

- IP66 complying with EN 60529
- NEMA 4 (single door) NEMA 12 (double door) complying with NEMA 250
- protection degree guaranteed by the two component foam seal
- impact resistance IK10 complying with EN62262.



WALL-MOUNTING BRACKETS

PART CODE: SDWC-010

Manufactured from zinc passivated sheet steel 2.5 mm.

Supply: 4 pieces.

Size conversions: 1U = 44.45mm = 1 3/4" 600mm = 24" 700mm = 28" 800mm = 32" 1kg = 2.2lbs